

# COILHOSE PRODUCTS



## COILHOSE CANNON®

The Cannon Extreme High Volume Air Blow Gun uses the compressed air from your in-plant or tow-behind compressor to clear heavy, stubborn debris.

- 9000-48S - 48" Extension Model
- 9000-24S - 24" Extension Model
- 9000-S - 2" Extension Model



9000-48S

- Clears surfaces of dust and debris; cleans and dries heavy equipment quickly and safely
- Uses compressed air from in-plant or tow-behind compressors, common on job sites
- Full range of extensions available

## REDI BURST™ POCKET BLOW GUN

**Same Power... Fits in your Pocket!**

The Redi-Burst Pocket Blow Gun delivers the same performance as larger thumb-lever blow guns, but is much smaller. Accepts all standard 1/8" Coilhose Pneumatics blow gun tips.



RB-KIT



- Easily stores in pocket, tool belt or tool box
- Engineered to deliver the same performance as larger blow guns
- Accepts standard 1/8" tips
- RB-KIT comes with standard safety and rubber tips

## Manifolds & Assemblies

Our Flat Hex Manifold is perfect for installations where space is limited or the assembly is required to lay low. Equipped with a single mounting hole, the flat hex can be nailed to a roof or joist during construction.

Contact the factory for a variety of available manifold styles and configurations.



- Available bare or equipped with 3 Six Ball Couplers
- Brass or Aluminum Construction
- Available types include: pigtail, high flow, straight, low profile, tri-pod, flat hex, swivel, tee and cross
- Assemblies are equipped with quality Coilhose couplers & connectors

## Universal Safety Exhaust (USE) Couplers

**One Coupling does it all!**

The 5-in-1 Safety Exhaust Coupler easily and safely connects with all major interchanges. Reduces the possibility of injury to nearby personnel or damage to surrounding equipment from a whipping hose that is disconnected while pressurized air is still in the line. This coupler is designed to remain connected to the plug until the downstream air is completely bled off.



3/8" 582USE\*

1/4" 150USE

1/2" 123USE\*



- Industrial
- Aro
- Automotive (Tru-Flate)
- Euro (Megaflo)
- Lincoln

- Easily connects under zero pressure
- Safely disconnects without hose whip

\* Please Note: In 3/8" and 1/2" body sizes, the Safety Exhaust Coupler works ONLY with the Industrial and Automotive Interchanges.

# COILHOSE PRODUCTS




## FLEXEEL & FLEXEEL *max*™

The Original

Our most popular hose. Reinforced Polyurethane hose with fittings that are reusable and can be quickly repaired in the field. Flexeel Max has even more added features like a higher working pressure, a ball swivel coupler, either in industrial or automotive interchange, an air safety plug, eel strap and hi-viz eel green color.



- Excellent flexibility in low temperatures
- 200 and 300 psi working pressure
- Reusable field-repairable fittings



### Max Extras:

- Ball Swivel increases maneuverability
- Air safety plug to disconnect safely without pressure
- Eel strap for easy storage

## Yellow Belly™

### HYBRID PVC AIR HOSE

Hybrid PVC/Rubber blend that offers excellent low temperature flexibility performance.



- Rolls out and stores easily
- Lays flat
- Strong brass fittings
- 300 psi working pressure



## FLEXCOIL®

FLEXCOIL is the finest polyurethane air hose on the market today and eliminates the two most common limitations of other self-storing air hoses: kinking and abrasion. This lightweight, yet extremely durable hose will withstand the rigors of tough industrial environments while maintaining its resiliency over a long period of time.



- Tough, durable, lightweight
- Excellent flexibility
- Fittings are field repairable
- Available in a variety of colors and configurations

## Air Tool Lubricant

Coilhose Air Tool Lubricant is specially formulated ISO 22 lubricant, designed to prolong the life of air tools and accessories. Available in Standard or Wintergrade, Air Tool Lubricant can keep your operation running all year.

ATL is available in 4 oz, 16 oz, 32 oz, 128 oz plastic bottles and in a 55 gallon drum; ATLW is available in 4 oz, 16 oz and 128 oz plastic bottles



- Inhibits the Formation of Rust
- Removes Moisture
- Temp Range: 50°F +
- Wintergrade Temp Range: -45°F +
- Made in USA

## Miniature Series Regulators

The Miniature Series Regulators are designed to be utilized in small spaces with limited flow requirements. Equipped standard with 0-125 psi regulator spring. All Miniature Series Regulators are a relieving design.



- For Installation in Compact Spaces
- Perfect for Control Panels and Miniature Pneumatic Circuits
- Made in USA with Domestic & Foreign Components