

GILAFLEX™

INNER-BRAIDED PVC AIR HOSE



SPECIAL BLEND PVC HAS NO MEMORY -
HOSE LAYS DOWN FLAT ON THE GROUND

VERY TIGHT BEND RADIUS -
HOSE WON'T KINK & CUT OFF AIR SUPPLY

STEEL SPRING STRAIN RELIEF -
PROTECTS HOSE AT ITS WEAKEST POINT (AT THE FITTING) WITHOUT INHIBITING MANEUVERABILITY

REUSABLE FITTINGS SUPPLIED AS STANDARD -
MAKES FIELD REPAIR QUICK & EASY

UV STABILIZED -
WON'T FADE OR DEGRADE DUE TO PROLONGED EXPOSURE TO LIGHT


CHEMICAL & ABRASION RESISTANT -
TOUGH ENOUGH TO WITHSTAND HARSH WORKING ENVIRONMENTS

SMOOTH OUTER COVER -
DOESN'T TRAP DIRT & EASY TO CLEAN

Working Pressure:
325 PSI @ 70° F



180° BEND RADIUS WITH STRAIN RELIEF



TOUGH • FLEXIBLE • DURABLE • SAFE • ECONOMICAL

ITEM DESCRIPTION	MODEL NUMBER
3/8" x 25' With 1/4" MPT RIGID FITTINGS	GF60254Q
3/8" x 50' With 1/4" MPT RIGID FITTINGS	GF60504Q
3/8" x 100' With 1/4" MPT RIGID FITTINGS	GF61004Q
3/8" x 200' BULK (NO FITTINGS)	GF6200Q
3/8" x 1/4" MPT GILAFLEX RIGID REUSABLE FITTING, WITH STRAIN RELIEF	GFRM0604SR



COILHOSE PNEUMATICS
East Brunswick, NJ
info@coilhose.com
www.coilhose.com